



**LEGENDARY
RELIABILITY
SINCE 1927**

Chain Tongs - Single Jaw



- » Hardened drop-forged jaws
- » Equipped with heat-treated chain
- » High-quality steel throughout
- » Replacement parts interchangeable with other standard brands

Specifications

Part No.	Pipe Size	Gripping Width	Tong Length	Weight
C11-P	1/8" - 1-1/2"	1.76"	20"	6 lbs.
C12-P	1/4" - 2-1/2"	2.25"	27"	10 lbs.
C13-P	3/4" - 4"	2.67"	37"	20 lbs.
C135-P	1" - 6"	2.89"	45"	27 lbs.
C14-P	1-1/2" - 8"	3.09"	51"	31 lbs.
C15-P	2" - 12"	3.35"	65"	56 lbs.
C16-P	4" - 18"	4.63"	87"	147 lbs.

**NOTE: Tongs are also available with extra long chains.
See product page on website.**

⚠ WARNING! Use as a hand tool only. Do Not Strike, use a "cheater" or extend handle. **SERIOUS INJURY** may result if used improperly. Read Safe Practices & Procedures Manual prior to operation. Follow OSHA, NSC, etc. standards, safe practices, and procedures. **⚠**

NOTE: Safe Practices & Procedures Manual can be found on pages 31-37 of this product guide.

Chain Tongs - Reversible



- » Turn pipe in either direction without removing from workpiece or unhooking chain
- » I-beam design handles and heat-treated forged jaws
- » Equipped with heat-treated chain
- » Replacement parts interchangeable with other standard brands

Specifications

Part No.	Pipe Size	Gripping Width	Tong Length	Weight
C27-P	1/4" - 2-1/2"	2.19"	27"	11 lbs.
C37-P	3/4" - 4"	2.69"	37"	19 lbs.
C47-P	1" - 6"	3.00"	47"	30 lbs.
C57-P	1-1/2" - 8"	3.38"	57"	42 lbs.
C67-P	2" - 12"	3.69"	67"	59 lbs.

**NOTE: Tongs are also available with extra long chains.
See product page on website.**

⚠ WARNING! Use as a hand tool only. Do Not Strike, use a "cheater" or extend handle. **SERIOUS INJURY** may result if used improperly. Read Safe Practices & Procedures Manual prior to operation. Follow OSHA, NSC, etc. standards, safe practices, and procedures. **⚠**

NOTE: Safe Practices & Procedures Manual can be found on pages 31-37 of this product guide.

Fitting Tongs



- » Work narrow or confined gripping areas
- » Easily applied and removed from workpiece
- » Equipped with heat-treated chain

Specifications

Part No.	Pipe Size	Gripping Width	Tong Length	Weight
C27-F	1/4" - 2-1/2"	.69"	23-1/4"	8 lbs.
C57-F	1-1/2" - 8"	1.13"	54-1/2"	32 lbs.

NOTE: Tongs are also available with extra long chains.
See product page on website.



WARNING! Use as a hand tool only. Do Not Strike, use a "cheater" or extend handle. SERIOUS INJURY may result if used improperly. Read Safe Practices & Procedures Manual prior to operation. Follow OSHA, NSC, etc. standards, safe practices, and procedures.



NOTE: Safe Practices & Procedures Manual can be found on pages 31-37 of this product guide.

Chain Tongs



- » Vee-shaped jaw
- » Grips in downward motion, ratchets in upward motion
- » Equipped with heat-treated chain
- » Sizes capable of delivering up to 3,000 ft.-lbs. torque

Specifications

Part No.	O.D.	Gripping Width	Handle Length*	Weight
STEEL				
CPA13	1-1/2" - 6"	2.62"	30"	18 lbs.
CPA14	2" - 10"	3.13"	44"	35 lbs.
ALUMINUM (for light-duty applications only)				
CPA14-L60AL	2" - 10"	3.13"	60"	25 lbs.

*Call factory for torque arm lengths.

>>> **Maximum Working Loads** <<<

Torques vary according to O.D.

See Torque Tables on product page of website.



WARNING! Do Not Exceed Maximum Working Load! Overloading may result in SERIOUS INJURY or DEATH! Always use a load cell or other calibrated indicating device to monitor the line pull on the tong to avoid overload. Read Safe Practices & Procedures Manual prior to operation. Follow OSHA, NSC, etc. standards, safe practices, and procedures.



NOTE: Safe Practices & Procedures Manual can be found on pages 31-37 of this product guide.