



Tubing Tongs



- » Design allows operator to “snap” the tool onto the workpiece for positive grip
- » Cam lever serves to both lock and open the jaws
- » Replaceable hardened steel bits

Specifications

Part No.	O.D.	Gripping Width	Handle Length	Weight
Medium Heavy Duty				
TMA2002375	2.375"	1.25"	31-1/2"	17 lbs.
TMA2502875	2.875"	1.25"	33-13/16"	19 lbs.
TMA2503063	3.063"	1.25"	33-13/16"	19 lbs.
TMA3003500	3.500"	1.25"	35"	25 lbs.
TMA3003668	3.668"	1.25"	35"	26 lbs.
TMA3504000	4.000"	1.25"	35-1/2"	28 lbs.
TMA3504250	4.250"	1.25"	35-1/2"	29 lbs.
Heavy Duty				
THA2002375	2.375"	2.00"	33-3/8"	27 lbs.
THA2502875	2.875"	2.00"	39-5/8"	30 lbs.
THA3003500	3.500"	2.00"	40"	35 lbs.

 **WARNING!** Use as a hand tool only. Do Not Strike, use a “cheater” or extend handle. **SERIOUS INJURY** may result if used improperly. 



TITAN™ Tubing Elevator



- » Equipped with a double locking retainer assembly for maximum safety
- » Made from heat-treated alloy steel for strength and durability
- » Flame hardened load collar for increased abrasion resistance
- » Manufactured and tested to API 8C

Specifications – API CERTIFIED

Part No.	Tubing Size	Weight	Rated Load
TEA035-238N	2-3/8" Non-Upset	53 lbs.	35 tons
TEA035-238U	2-3/8" External Upset	53 lbs.	35 tons
TEA035-278N	2-7/8" Non-Upset	52 lbs.	35 tons
TEA035-278U	2-7/8" External Upset	52 lbs.	35 tons
TEA100-238N	2-3/8" Non-Upset	116 lbs.	100 tons
TEA100-238U	2-3/8" External Upset	116 lbs.	100 tons
TEA100-278N	2-7/8" Non-Upset	114 lbs.	100 tons
TEA100-278U	2-7/8" External Upset	114 lbs.	100 tons
TEA100-312N	3-1/2" Non-Upset	112 lbs.	100 tons
TEA100-312U	3-1/2" External Upset	112 lbs.	100 tons

 **WARNING!** Improper use of tubing elevators may result in **INJURY** or **DEATH!** Do Not Exceed Rated Load! Follow safe practices listed in Data Book. 



License
No. 8C-0069