

Chamfer Tools - Drill Powered

FEATURES

- Quickly chamfers pipe for solvent connections.
- Features strong, aluminum body and 3/8 inch hex, steel shaft.
- Uses drill power which eliminates user fatigue when making multiple cuts/chamfers.
- Deburrs inside and outside simultaneously, in just seconds.
- Produces smooth, consistent chamfer on plastic pipe, eliminating leaky glue joints that can be caused by improper chamfer.

Catalog	Item Code	Description		Pipe Capacity	Weight	
No.			in- nom.	actual O.D. mm	lbs	kg
PBKIT	04660	Kit with 2", 3" and 4" tools with case	-	-	6.6	3.0
PB2	04662	for 2" plastic pipe	2	52.2 ID / 60.3 OD actual	0.4	0.2
PB3	04663	for 3" plastic pipe	3	77.9 ID / 88.9 OD actual	0.5	0.2
PB4	04664	for 4" plastic pipe	4	102.2 ID / 114.3 OD actual	0.7	0.3

PEX Crimpers

FEATURES

- REED tool crimps rings easily, giving good connections.
- PEX Crimper are the right tools for PEX systems and properly seal the rings without distortion.
- Each REED copper ring crimper includes a go/no-go gauge and an Allen wrench.

Catalog	Item	.	Weight	
No.	Code	Description	lbs	kg
△ PXCR12S	04900	¹ /2" capacity with 8 ³ /4" hand l e	3.0	1.4
△PXCR34S	04903	³ /4" capacity with 9" handle	3.0	1.4
△ PXCR1M	04904	1" capacity with 11 ¹ /2" hand l e	4.0	1.8
△PXCR1234M	04910	¹ /2" - ³ /4" capacity with 11 ¹ /2" hand l e	4.3	1.9
△ PEXOH12	04920	¹ /2" capacity, one hand style	2.5	1.1
△PEXOH34	04925	³ /4" capacity, one hand style	2.6	1.2
FEXOR34	04925	~/4" capacity, one nana style	2.0	I.Z

Handle length does not include head.



PEPEEL12

in use

PE Pipe Peeler

FEATURES

- One tool does a range of pipe.
- Creates a uniformly peeled surface.
- Works well even on out-of-round pipe.
- Strong thermoplastic rollers and plated sides on chain resist corrosion.

Catalog No.	Item Code	Pipe Ca	Weight		
		in-nom.	actual O.D. mm	lbs	kg
PEPEEL6	04631	1 ¹ / ₂ - 6 *	48 - 168	3.1	1.4
PEPEEL12	04632	6 - 12	168 - 324	10.9	5.0

*O.D. must be 1.9" (48.3 mm) or more









PEPEEL6

True Peel® PE Prep Tools

FEATURES

- Prepares the ends of PE pipe and tapping tees for electrofusion.
- Removes 0.009" 0.12" (0.23 mm 0.3 mm) peel thickness.
- Spring actuated blade gives a complete peel, even on out-of-round pipe.
- Observation window indicates the completion of the peel.
- Close fitting mandrel rounds pipe that may be oval.
- Hardened tool steel cutting blade with two cutting edges for twice the life.
- Includes a protective carrying case.

Catalog	Item	D	Weight	
No.	Code	Description	lbs	kg
PEP50CTS7	04634	Fits ¹ /2" CTS SDR7 0.090 Wall	0.9	0.41
PEP75IPS11	04635	Fits ³ /4" IPS DR11 0.095 Wall	1.2	0.54
PEP1IPS7	04624	Fits 1" IPS DR7 0.188 Wall	1.4	0.6
PEPICTS7	04627	Fits 1" CTS SDR7 0.161 Wall	1.3	0.6
PEPICTS115	04636	Fits 1" CTS SDR11.5 0.099 Wall	1.3	0.6
PEP1IPS11	04637	Fits 1" IPS DR11 0.120 Wall	1.4	0.6
PEP125IPS10	04626	Fits 1 ¹ /4" IPS DR10 0.166 Wall	1.9	0.9
PEP125IPS11	04638	Fits 1 ¹ /4" IPS DR11 0.151 Wall	1.9	0.9
PEP125CTS11	04625	Fits 1 ¹ /4" CTS SDR11 0.121 Wall	1.5	0.7
PEP2IPS11	04639	Fits 2" IPS DR11 0.216 Wall	3.1	1.4

TRUE PEEL® METRIC

Catalog No.	Item Code	Description
PEP32MM	04680	Fits 32mm DR11, 3.0 mm Wall
PEP40MM	04681	Fits 40mm DR11, 3.7 mm Wall
PEP63MM	04683	Fits 63mm DR11, 5.8 mm Wall











FEATURES

- Ground the work area to increase safety for the operator.
- · Static electricity grounding can dissipate the charge and minimize the possibility of ignition.
- 7 foot cable provides convenient working distance from tool to ground.
- Half inch probe diameter of PEGR7 provides strength and reduces buckling.

Catalog No.	Item Code	Description	Weight		
		Description	lbs	kg	
PEGR7*	04621	Set screw lugs, 7 ft. cable	1.3	0.6	
PEGRM*	04622	Magnet connection, 7 ft. cable	0.6	0.3	

*EXCLUSIVE FEATURES: PEGR7 stocky probe diameter, PEGRM magnet connection



Observation

PEP75IPS11

PEP1CTS115

PEP40MM